

Technical data sheet

Austrotherm EPS[®] 150

Description:	Expanded polystyrene boards for insulation with particularly high strength loads in construction																																																																																
Application:	For thermal insulation of flat roofs (passable), under screed and anywhere where high compressive strengths are required structurally																																																																																
Format:	Plates with a length of 1000 mm , a width of 500 mm , thicknesses from 20 to 400 mm Edge shape: Straight edge (GK)																																																																																
Quantity in package:	<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Thickness (mm)</th> <th>Length x width (mm)</th> <th>Number of plates</th> <th>Area (m²)</th> <th>R_D m² K²/W</th> </tr> </thead> <tbody> <tr><td>20</td><td>1000x500</td><td>24</td><td>12.0</td><td>0.60</td></tr> <tr><td>30</td><td>1000x500</td><td>16</td><td>8.0</td><td>0.90</td></tr> <tr><td>40</td><td>1000x500</td><td>12</td><td>6.0</td><td>1.20</td></tr> <tr><td>50</td><td>1000x500</td><td>10</td><td>5.0</td><td>1.50</td></tr> <tr><td>60</td><td>1000x500</td><td>8</td><td>4.0</td><td>1.80</td></tr> <tr><td>70</td><td>1000x500</td><td>7</td><td>3.5</td><td>2.10</td></tr> <tr><td>80</td><td>1000x500</td><td>6</td><td>3.0</td><td>2.40</td></tr> <tr><td>90</td><td>1000x500</td><td>5</td><td>2.5</td><td>2.70</td></tr> <tr><td>100</td><td>1000x500</td><td>5</td><td>2.5</td><td>3.00</td></tr> <tr><td>120</td><td>1000x500</td><td>4</td><td>2.0</td><td>3.60</td></tr> <tr><td>140</td><td>1000x500</td><td>4</td><td>2.0</td><td>4.20</td></tr> <tr><td>150</td><td>1000 x 500</td><td>3</td><td>1.5</td><td>4.50</td></tr> <tr><td>160</td><td>1000x500</td><td>3</td><td>1.5</td><td>4.80</td></tr> <tr><td>180</td><td>1000x500</td><td>3</td><td>1.5</td><td>5.45</td></tr> <tr><td>200</td><td>1000x500</td><td>2</td><td>1.0</td><td>6.05</td></tr> </tbody> </table>	Thickness (mm)	Length x width (mm)	Number of plates	Area (m ²)	R _D m ² K ² /W	20	1000x500	24	12.0	0.60	30	1000x500	16	8.0	0.90	40	1000x500	12	6.0	1.20	50	1000x500	10	5.0	1.50	60	1000x500	8	4.0	1.80	70	1000x500	7	3.5	2.10	80	1000x500	6	3.0	2.40	90	1000x500	5	2.5	2.70	100	1000x500	5	2.5	3.00	120	1000x500	4	2.0	3.60	140	1000x500	4	2.0	4.20	150	1000 x 500	3	1.5	4.50	160	1000x500	3	1.5	4.80	180	1000x500	3	1.5	5.45	200	1000x500	2	1.0	6.05
Thickness (mm)	Length x width (mm)	Number of plates	Area (m ²)	R _D m ² K ² /W																																																																													
20	1000x500	24	12.0	0.60																																																																													
30	1000x500	16	8.0	0.90																																																																													
40	1000x500	12	6.0	1.20																																																																													
50	1000x500	10	5.0	1.50																																																																													
60	1000x500	8	4.0	1.80																																																																													
70	1000x500	7	3.5	2.10																																																																													
80	1000x500	6	3.0	2.40																																																																													
90	1000x500	5	2.5	2.70																																																																													
100	1000x500	5	2.5	3.00																																																																													
120	1000x500	4	2.0	3.60																																																																													
140	1000x500	4	2.0	4.20																																																																													
150	1000 x 500	3	1.5	4.50																																																																													
160	1000x500	3	1.5	4.80																																																																													
180	1000x500	3	1.5	5.45																																																																													
200	1000x500	2	1.0	6.05																																																																													
Product type:	Other thicknesses, slab formats – upon request.																																																																																
Designation:	Expanded polystyrene (EPS) according to EN 13163 EPS[®] 150 marking on the short side of the package																																																																																
Designation code:	EPS-EN 13163-T1-L2-W2-Sb2-P5-DS(N)2-DS(70,-)1-BS300-CS(10)150-TR280-WL(T)2-MU(30÷70)																																																																																
Technical data:	<table border="0" style="width: 100%;"> <tr> <td>Thermal conductivity λ :</td> <td style="text-align: right;">≤ 0.0 33 W/mK</td> </tr> <tr> <td>Compressive strength (CS) :</td> <td style="text-align: right;">≥ 150 kPa</td> </tr> <tr> <td>Bending strength (BS):</td> <td style="text-align: right;">≥ 300 kPa</td> </tr> <tr> <td>Tensile strength (TR):</td> <td style="text-align: right;">≥ 280kPa</td> </tr> <tr> <td>Water absorption during prolonged full immersion:</td> <td style="text-align: right;">≤ 2 % by volume</td> </tr> <tr> <td>Water vapor diffusion resistance number μ:</td> <td style="text-align: right;">30-70</td> </tr> <tr> <td>Reaction to fire class:</td> <td style="text-align: right;">E</td> </tr> </table>	Thermal conductivity λ :	≤ 0.0 33 W/mK	Compressive strength (CS) :	≥ 150 kPa	Bending strength (BS):	≥ 300 kPa	Tensile strength (TR):	≥ 280kPa	Water absorption during prolonged full immersion:	≤ 2 % by volume	Water vapor diffusion resistance number μ:	30-70	Reaction to fire class:	E																																																																		
Thermal conductivity λ :	≤ 0.0 33 W/mK																																																																																
Compressive strength (CS) :	≥ 150 kPa																																																																																
Bending strength (BS):	≥ 300 kPa																																																																																
Tensile strength (TR):	≥ 280kPa																																																																																
Water absorption during prolonged full immersion:	≤ 2 % by volume																																																																																
Water vapor diffusion resistance number μ:	30-70																																																																																
Reaction to fire class:	E																																																																																
Application temp.:	Up to 85°C.																																																																																
Processing:	According to work instructions and construction safety instructions																																																																																

Austrotherm EPS[®] does not contain chlorofluorocarbons (CFCs), HFCs, HFCS, or HBCD .